


Making the connection

Tze Chiew Product Sales Manager




IoT Stack




Device Lifecycle Management (Deploy, Monitor, Service, Manage, Update, Decommision)





IT and OT speak different languages.





Traditional products used in a new way









Visualization and Action

SERVICE

Wired and wireless analog/digital I/Os
Protocol converters
RS-4xx, MODBUS/RTU and MODBUS/TCP
ETHERNET/IP, PROFINET
ETH, WIFI
Wifi, HTTP, RESTful APIs, MQTT

A huge portfolio of traditional products used in a new way.



New IoT-ready products



Data Ingestion and Storage

Data

Transformation



and Action



Visualization SERVICE

Sensor nodes with data-logging Indoor/outdoor RESTful API and MQTT





Industry 4.0







Wi-Fi



ZigBee



Sub 1G



LoRaWAN



3G/LTE















Proximity

Local Area

Neighborhood area

Wide Area

WISE-4000

IoT WiFi I/O Module



- Wi-Fi
- Direct connection
- Data Storage
- MQTT
- Restful

WISE-4200

Industrial IoT Wireless Sensor Node



- Data Storage
- Math
- LoRa to WiFi/LAN



WISE-4400

IP65-Rated IoT Wireless Sensor Node

• LoRa



- SMS
- IP 65-rated
- Built-in Antenna
- LoRa to WiFi/LAN



WISE-4600

Outdoor IoT Wireless Sensor Node

- LoRaWAN/Cellular
- Support M2.Com
- IP65-rated









Enabling an Intelligent Planet

Building-blocks enabling intelligent IoT products




m2.COM





Visualization SERVICE



and Action



m2.COm WISE-1500 Wireless Sensor Series

Wide Area Neighborhood area Local Area



WISE-1520

- TI Cortex-M4 80MHz
- RAM 256 KB / 1MB Flash
- Low-power Wi-Fi 802.11 b/g/n with AES 128 Encryption
- TI-RTOS support

WISE-1540

- STM Cortex-M4 80MHz
- Linear Dust SmartMesh
- Self-forming & self-healing network
- IEEE 802.15.4e & 6LowPAN
- mbed OS Support

WISE-1570



ARM mbed

- ARM Cortex -M4 80MHz
- RAM 128KB / 1MB Flash
- Rel .14 NB-IOT Compliant
- Support multi-bands
- mbed OS support



- STM Cortex-M4 100 MHz
- RAM 256 KB / 1MB Flash
- Wi-Fi/Bluetooth Combo
- SIG compliant
- RTOS support



Wi Fi)



WISE-1510

- STM Cortex-M4 80 MHz
- RAM 64 KB / 256 KB Flash
- Sub 1 GHz 868/915MHz
- Support Private LoRa / LoRaWAN

ARM mbed

mbed OS Support

WISE-1511

- STM Cortex-M4 80MHz
- RF: NXP OL2385
- RC1 EU: 868MHz
- RC3 JP: 920MHz
- SigFox Ready



ARM

LoRa





Flexible, scalable, powerful gateways








Visualization and Action

SERVICE

x86 QUARK, ATOM and CORE i ARM Any wired/wireless connectivity Analog/DIGITAL I/Os





Key role in security

EDGE Computing



Low-latency command and control to respond to operational data with ultra-low latency and enable real-time decisions.

Limited connectivity to the cloud to analyze and react to data even when cloud connectivity is intermittent.

Limited bandwidth thanks to the aggregation and pre-filtering of data before sending it to the cloud.

Compliance: regulatory compliance may require some data to be locally anonymized or aggregated before being sent to the cloud.



Edge Intelligent Server





EIS-D110/EIS-D120/EIS-D150

Building Up Edge-to-Cloud Applications with Integrated Hardware plus Software

Accelerates IoT implementation through an integrated HW/SW solution that enable IoT connectivity, data manageability and analytics.

(WISE-PaaS software packages, IoT development tools, pre-configured cloud services, WISE-PaaS marketplace).





Visualization and Action

SERVICE

WISE-PaaS
Built-in

WISE-PaaS/RMM
Remote Monitoring and Management


WISE-PaaS/Security
Centralize Security
Management

WebAccess/SCADA
Smart SCADA
Smart SCADA

WISE-PaaS/OTA
Remote Software
Update

WebAccess/IMM
Interactive Multimedia


WebAccess/HMI
Human Machine
Interface













arm MBED Products

MBED EDGE



MBED OS



WISE-3610



EPC-R4760 🦓



WISE-1510 LoRa



WISE-3620



EPC-R4610



WISE-1520 WiFi



EPC-R4760



UBC-220



WISE-1530 WiFi/BLE



EPC-R4610





WISE-1540 Dust



EPC-R4680




UBC-222



WISE-1570 NB-IoT





- · Embedded within a wide-range of wireless sensor nodes
- · Designed for multi-applications











Data communication

Remote management

Flexible identity provisioning

End-to-end security





GREENGRASS





UTX-3117





ARK-1123



WISE-1520






EPC-R4760

ARK-1124






EIS-D210



Embedding Lamba Compute (and other AWS Services) in Connected Devices extends AWS cloud capabilities to local devices









Industry 4.0 Solution Ready Platform



Automation







and Action



Visualization SERVICE



30+ vendors





Cold Chain Logistics – real-time monitor



Cold chain Sensor



In-vehicle gateway

Backend control center



ADVANTECH Enabling an Intelligent Planet

User Scenario

Before Departing

Operator



Driver



Setup Sensor & Initial

- 5 Second setup
- Setup via NFC reader
- Setup Temp. Limit/record time
- Check Battery capacity
- Initial by SW or button

During Transport



Logging & monitoring

- Monitoring the status of goods and vehicle
- Coach the driver in real time and alert the backend office

After Delivery





Management

- Record and update the data to backend office by SW API or SDK
- Check if any cold chain breach

Sensors NFC reader Config Tool







In-vehicle Gateway



Cloud Service








Android apk

Greenhouse





Edge Intelligent Server Starter Kit





EIS-DK10

- Complete IoT Connection Solutions
- All-in-one Developer Packages
- Plug-and-Play to Jumpstart IoT Innovation

Including: 1 month Azure VM



- Injection
- · IoT Protocols
- Light Analytics



Storage

- · ODBC/SQL DB
- NoSQL DB



Security

- Intel Security
- · SSL/TLS



Dashboard

- Mobile Device Support
- Data Insight



Making the connection

OT & IT
Hardware & Software
Physical & Digital
Human

Nobody can do I(o)T alone

Let's do I(o)T together

tze.chiew@Advantech.nl

